



# Declaration of Performance EN



Regulation No. 305/2011  
DOP-Green 150 2589

1. Unique identification code of product-type	pellet Stove
2. Product name	Green 150 series
3. Intended use or uses of the construction product, in accordance with the applicable technical specification	Room heating appliance, fueled by pellets without hot water supply
4. Name and contact address of the manufacturer	Heta A/S, Jupitervej 22, DK-7620 Lemvig. heta@heta.dk
5. Where applicable, name and contact address of authorized representative. E-mail.	Martin Bach, E-mail: martin.bach@heta.dk
6. System of assessment and verification of constancy of performance of the construction product	System 3
7. Notified body relevant to the assessment and verification of constancy of performance	Danish Technological Institute, DK-8000 Aarhus Notified body No. 1235. Report nr. 300-ELAB-2589-EN

## 8. Declared Performance

Harmonized technical specification	EN 14785:2006 Nominal output	EN 14785:2006 Low output
Emission	CO 0,006%/73 mg/m <sup>3</sup> <sub>n</sub> Nox 181 mg/m <sup>3</sup> <sub>n</sub> Dust 15 mg/m <sup>3</sup> <sub>n</sub> Dust (NS3058/3059) --- g/kg OGC (CEN/TS 15883) 4 mgC/m <sup>3</sup> <sub>n</sub> ved 13% O <sub>2</sub> Energy consumption 66 W/h	CO 0,023%/288 mg/m <sup>3</sup> <sub>n</sub> Nox 184 mg/m <sup>3</sup> <sub>n</sub> Dust 18 mg/m <sup>3</sup> <sub>n</sub> Dust (NS3058/3059) --- g/kg OGC (CEN/TS 15883) 18 mgC/m <sup>3</sup> <sub>n</sub> ved 13% O <sub>2</sub> Energy consumption 44 W/h

## Fire safety

Reaction to fire	A1
Test of fire safety in connection with the burning of wood	Approved
Distance to combustible materials	Minimum distances in mm
Rear	60
Sides distance to combustible materials	90
Distance to floor from lower edge of the door	---
Furniture distance	770

## Safety

Mechanical resistance (to carry a chimney / flue)	Not tested (NPD)
Electrical safety	Pass
Surface temperature	Pass
Cleanability	Pass

## Thermal output

Nominal heat output	3,6-7,3 kW
Room heat output	3,6-7,3 kW
Energy efficiency	η 96%-94%
Fluegas temperature at nominal heat output	T 55°C-87°C
Water heating output	NA (NPD)
Maximum water operating pressure	NA (NPD)

## 9.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf the manufacturer of 05-01-2023

**Heta A/s**

JUPITERVEJ 22 - DK-7620 LEMVIG  
Tlf. +45 9663 0600 FAX +45 9663 0616  
Martin Bach

After the 05-01-2023 change of the above-mentioned production type this Declaration of Performance becomes invalid.

Heta A/S, Jupitervej 22, DK-7620 Lemvig, Tlf. +45 9663 0600, www.heta.dk