

Ecodesign EU Declaration of Conformity

DoC E4-32 Scanline 8 104450111LHD-001 2020 Product fiche



Manufacturer	Heta A/S
Adress	Jupitervej 22, DK 7620 Lemvig
E-mail	heta@heta.dk
Website	www.heta.dk
Telephone	+45 9663 0600

Model identifier | Scan-Line 8 Gas G30 (E4-32 Scanline 8)

The identified product described above is in conformity with:		
The relevant EU harmonized regulations:		
REG (EU) 2016/426		
REG (EU) 2015/1185		
REG (EU) 2015/1186		
The relevant harmonized standards		
BSEN 613:2001+A1:2008		

Characteristics when operating with the preferred fuel only				
Heat output				
Item	Symbol	Value/Unit		
Nominal heat output	P _{nom}	6,8 kW		
Minimum heat output	P _{min}	1,6 kW		
Useful efficiency (NCV as received)				
Useful efficiency at nominal heat output	η _{th, nom}	90%		
Useful efficiency at minimum heat output	η _{th, min}	59%		
Auxiliary electricity consumption				
At nominal heat output	el _{max}	9 ⁻⁵ kW		
At minimum heat output	el _{min}	9 ⁻⁵ kW		
In standby mode	el _{sb}	9 ⁻⁵ kW		

Type of heat output/room temperature control		
single stage heat output, no room temperature control	Yes	
two or more manual stages, no room temperature control	No	
with electronic room temperature contro	No	
with electronic room temperature control	No	
with electronic room temperature control plus day timer	No	
with electronic room temperature control plus week timer	No	

Other control options		
room temperature control, with presence detection	No	
room temperature control, with open window detection	No	
with distance control option	No	

Notified body relevant to the assessment and verification of	
constancy of performance	

Intertek Total quality. Assured IGP, 4 Oak Business Units, Thorverton Road, Exeter EX2 8FS Notified body No. 0359. Report No. 104450111LHD-001

Fuel	Preferred fuel	Other suit- able fuel
Wood logs with moisture content ≤ 25 %	No	No
Compressed wood with moisture content < 12 %	No	No
Other woody biomass	No	No
Non-woody biomass	No	No
Anthracite and dry steam coal	No	No
Hard coke	No	No
Low temperature coke	No	No
Bituminous coal	No	No
Lignite briquettes	No	No
Peat briquettes	No	No
Blended fossil fuel briquettes	No	No
Blended biomass and fossil fuel briquettes	Yes	No
Other blend of biomass and solid fuel	No	No

Emissions at			mg/Nm³ (13 % O ₂)	
nominal heat output	η _s %	PM	OGC	СО	NO _x
output	≥ 65	≤ 40	≤ 120	≤ 1500	≤ 200
	80	-	-	18	18

Technical documentation	
Indirect heating functionality:	No
Direct heat output:	6,8 kW
Energy Efficiency Index (EEI):	EEI 89
Fluegas temperature at nominal heat output	T 363°C
Energy efficiency class	A

Safty	
Reaction to fire	A1
Test of fire safety in connection with the burning of wood	Approved
Distance to combustible materials Rear. Without insulation / with insulation Sides distance to combustible materials Furniture distance	Minimum distances in mm 120/120 350 850

Signed on behalf the manufacturer of 07.02.2022



The chimney sweep's signature	Date
Signature	