

# Declaration of Performance EN

#### Regulation No. 305/2011 DOP-Green 250 2559

1. Unique identification code of product-type	pellet Stove	
2. Product name	Green 250 series	
3. Intended use or uses of the construction product, in accordance with the applicable technical specification	Room heating appliance, fueled by pellets without hot water supply	
4. Name and contact address of the manufacturer	Heta A/S, Jupitervej 22, DK-7620 Lemvig. heta@heta.dk	
5. Where applicable, name and contact address of authorized representative. E-mail.	Martin Bach, E-mail: martin.bach@heta.dk	
6. System of assessment and verification of constancy of performance of the construction product	System 3	
7. Notified body relevant to the assessment and verification of constancy of performance	Danish Technological Institute, DK-8000 Aarhus Notified body No. 1235. Report nr. 300-ELAB-2559-EN_rev. 1	

# 8. Declared Performance

Harmonized technical specification	EN 14785:2006 Nominel output		EN 14785:2006 Low o	utput
Emission	CO	0,003%/31mg/m <sup>3</sup> n	CO	0,017%/218mg/m <sup>3</sup> n
	Nox	168 mg/m <sup>3</sup> n	Nox	170 mg/m <sup>3</sup> n
	Dust	18 mg/m <sup>3</sup> n	Dust	18 mg/m <sup>3</sup> n
	Dust (NS3058/3059)	g/kg	Dust (NS3058/3059)	g/kg
	OGC (CEN/TS 15883)	2 mgC/m <sup>3</sup> n ved 13% O <sub>2</sub>	OGC (CEN/TS 15883)	8 mgC/m <sup>3</sup> n ved 13% O <sub>2</sub>
	Energy consumption	60 W/h	Energy consumption	43 W/h

# Fire safety

Reaction to fire	A1
Test of fire safety in connection with the burning of wood	Approved
Distance to combustible materials Rear Sides distance to combustible materials Distance to floor from lower edge of the door Furniture distance	Minimum distances in mm 80 150  650

#### Safety

Mechanical resistance (to carry a chimney / flue)	Not tested (NPD)
Electrical safety	Pass
Surface temperature	Pass
Cleanability	Pass

### Thermal output

Nominal heat output	3,7-8,8 kW
Room heat output	3,7-8,8 kW
Energy efficiency	<b>η</b> 97%-95%
Fluegas temperature at nominal heat output	T 47°C-87°C
Water heating output	NA (NPD)
Maximum water operating pressure	NA (NPD)

<sup>9.</sup> 

The performance of the product identified in points1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf the manufacturer of 05-01-2023



TLEASE 9663 0600 and 4550 and 5000 mentioned production type this Declaration of Performance becomes invalid.