



HETA Declaration of Performance EN

Regulation No. 305/2011
DOP-Scan-Line 7 2534-2020

| | |
|--|---|
| 1. Unique identification code of product-type | Stove |
| 2. Product name | Scan-Line 7A, 7B, 7C, 7D,7L, 7D Low |
| 3. Intended use or uses of the construction product, in accordance with the applicable technical specification | Room heater burning solid fuel without hot water supply |
| 4. Name and contact address of the manufacturer | Heta A/S, Jupitervej 22, DK-7620 Lemvig. heta@heta.dk |
| 5. Where applicable, name and contact address of authorized representative. E-mail. | Factory Manager Martin Bach, E-mail: martin.bach@heta.dk |
| 6. System of assessment and verification of constancy of performance of the construction product | System 3 |
| 7. Notified body relevant to the assessment and verification of constancy of performance | Danish Technological Institute, DK-8000 Aarhus Notified body No. 1235. Report nr. 300-ELAB-2534-EN |

8. Declared Performance

| | |
|------------------------------------|---|
| Harmonized technical specification | EN 13240:2001/A2:2004 |
| Emission | CO 0,08% / 1009 mg/Nm ³ Nox 78 mg/Nm ³ Dust 15 mg/Nm ³ Dust (NS3058/3059) 2,18 g/kg OGC (CEN/TS 15883) 90 mgC/Nm ³ ved 13% O ₂ |

Fire safety

| | |
|--|-------------------------|
| Reaction to fire | A1 |
| Test of fire safety in connection with the burning of wood | Approved |
| Distance to combustible materials | Minimum distances in mm |
| Rear | 100 |
| Sides distance to combustible materials | 100 |
| Distance to floor from lower edge of the door | --- |
| Furniture distance | 800 |

Safety

| | |
|---|------------------------|
| Mechanical resistance (to carry a chimney / flue) | Not tested (NPD) |
| Electrical safety | NA (NPD) |
| Surface temperature | Approved |
| Cleanability | No specification (NPD) |

Thermal output

| | |
|--|------------|
| Nominal heat output | 4,5 kW |
| Room heat output | 4,5 kW |
| Energy efficiency | η 83% |
| Fluegas temperature at nominal heat output | T 243°C |
| Water heating output | NA (NPD) |
| Maximum water operating pressure | NA (NPD) |

9.

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed on behalf the manufacturer of 20.12.2022

Heta A/s

JUPITERVEJ 22 - DK-7620 LEMVIG

Interfering with the above-mentioned production type this Declaration of Performance becomes invalid.

Tlf. +45 9663 0600 - FAX +45 9663 0616
Martin Bach A/S, Jupitervej 22, DK-7620 Lemvig, Tlf. +45 9663 0600, www.heta.dk